

View product details



**USB-C** **HDMI** **4K**

PureLink's PushGo Alta transforms any small room into a fully equipped, connected meeting space – no setup, programming, or IT support required. Each system arrives pre-configured and ready to perform. Simply connect your devices, power on, and the technology handles the rest. Once connected, Alta routes crisp 4K video to your display and clear, evenly balanced audio through your speakers. From the sleek 10" touchscreen, you can switch inputs, manage connected sources, or adjust room settings such as lights or shades – all with a single tap. PushGo Alta also supports flexible multiview layouts, allowing multiple sources to be displayed simultaneously for collaborative discussions and side-by-side comparisons. Bringing the comfort and intelligence of smart-home automation into your workspace, PushGo Alta turns everyday meetings into seamless, polished experiences.

*Customization Available: Enjoy complimentary logo placement on your touchscreen. After your order, we'll contact you to finalize details. Additional interface or hardware customizations are available for an added cost.*

## Key Features

- Fully pre-programmed and ready to use
- Plug-and-play for same-day setup
- Premium 10" touchscreen control
- Stunning 4K video and high-quality audio output
- Supports up to four HDMI devices
- Flexible multiview display for multiple sources
- Compatible with Zoom, Microsoft Teams, Webex, and more
- Includes all essential hardware and cables
- Complimentary logo branding on touchscreen
- Perfect for huddle rooms and small meeting spaces

## Specifications

---

### ICON-T10

#### Standards & Compliance

Control Protocol	LAN (TCP/IP), RS-232 (bi-directional), RS-485 (bi-directional)
------------------	--

#### Communications & Control

Control Ports	LAN, RS-232, RS-485
Control Connector Type	RJ45, Mini phoenix (3.81mm)

#### Mechanical Features

Touch Panel Size	10 in
Touch Panel Resolution	1280x800
Touch Type	Capacitive Touch Screen
Network Port	LAN (RJ45)
RS-232/485 Port	1 x 3-pin - 3.81mm phoenix connector

#### Power

Power Input	PoE (IEEE 802.3af), DC 24V/1A via 2-pin phoenix
Power Consumption	6W (max)

#### Enclosure

Mounting Option	Table
Product Dimensions (W × D × H)	9.66 in × 6.46 in × 1.06 in (245.36mm × 164.08mm × 26.92mm)
Weight	1.96 lbs (889g)

#### Warranty

Parts	5 year
Labor	5 year

### ICON-E1

#### Standards & Compliance

Control Protocol	LAN (TCP/IP), RS-232 (bi-directional), IR, I/O
------------------	--

#### Communications & Control

Control Ports	LAN, RS-232, IR, I/O, RS-485
Control Connector Type	RJ45, Mini phoenix (3.81mm)

#### Power

Power Input	PoE (IEEE 802.3af), 12-24V DC / 1A via 2-pin phoenix
Power Consumption	6W (max)

#### Enclosure

Product Dimensions (W × D × H)	3.69 in × 2.63 in × 0.38 in (93.7mm × 66.8mm × 9.7mm)
Weight	0.65 lbs (295g)

#### Warranty

Parts	5 year
Labor	5 year

### MVS-41

#### Standards & Compliance

Signal Standards	HDMI 2.0b
HDCP	HDCP 2.2

#### Connector Types

HDMI Inputs	4 x HDMI IN (Type A, 19-pin female)
HDMI Outputs	1 x HDMI OUT (Type A, 19-pin female)
Control	RS-232 3-pin - 3.81mm phoenix connector (bi-directional), IR 3.5mm jack
SPDIF (RCA)	Yes
Audio Inputs	Analog (stereo balanced)
Audio Outputs	Analog (stereo balanced)
Dante	Yes

### Performance

Max Video Resolution	4K60 (4:4:4)
Video Bandwidth	18 Gbps
Color Space	RGB, YPbPr, YCbCr
Color Depth	8-bit
MTBF	60,000 – 120,000 hours
HDMI Audio Format	PCM 2.0, Dolby Digital, DTS

### Communications & Control

Control Ports	RS-232, IR
IR Remote	Yes
Control Connector Type	3.5mm TRS, Mini phoenix (3.81mm)

### Power

Power Input	AC 100 - 240V 50/60Hz
Power Supply	DC 12V/2.5A
Power Consumption	10W (max)

### Enclosure

Rack Mounting Option	No
Product Dimensions (W × D × H)	8.66 in × 3.94 in × 1.18 in (219.96mm × 100.08mm × 29.97mm)
Weight	1.37 lbs (620g)

### Warranty

Parts	5 year
Labor	5 year

### *TL-SG108PE 8 port switch*

### Connector Types & Features

Ports	4 x PoE+ ports, 8 x Gigabit RJ45 ports
Switching Capacity	16 Gbps
Packet Forwarding Rate	11.9 Mpps
Packet Buffer Memory	1.5 Mb
Jumbo Frame	15 KB

### Power

Power Consumption	74.27W (max)
-------------------	--------------

### Enclosure

Product Dimensions (W x D x H)	6.2 in x 4.0 in x 1.0 in (158mm x 101mm x 25mm)
--------------------------------	---

### Warranty

Parts	3 year
Labor	3 year