

[View product details](#)



iCON™ **USB-C** **HDMI** **4K**

PureLink's PushGo Aspen delivers higher performance and versatility for modern conference rooms and training environments. It arrives fully pre-programmed and ready for same-day use – just connect, power on, and start collaborating. PushGo Aspen supports up to six connected devices, including laptops, tablets, and phones, via HDMI or USB-C. Its integrated multiview processor lets you display multiple sources at once – perfect for side-by-side comparisons, group sessions, or multi-presenter meetings. Ultra-detailed 4K60 video and rich, room-filling sound ensure that every presentation looks sharp and sounds precise. At the center is a refined 10" touchscreen that unites every function – switching sources, managing displays, and adjusting lights or shades – into one elegant, intuitive interface. PushGo Aspen gives any room the sophistication of a professional-grade system, without the complexity of one.

Customization Available: Enjoy complimentary logo placement on your touchscreen. After your order, we'll contact you to finalize details. Additional interface or hardware customizations are available for an added cost.

Key Features

- Fully pre-programmed and ready to use
- Plug-and-play for same-day setup
- Premium 10" touchscreen control
- Brilliant 4K60 video and crystal-clear audio output
- Supports up to six HDMI or USB-C devices
- Flexible multi-view display for showing multiple sources at once
- Works with Zoom, Microsoft Teams, Webex, and more
- Includes all essential hardware and cables
- Complimentary logo branding on touchscreen
- Perfect for conference rooms, training spaces, offices, and more

Specifications

ICON-T10

Standards & Compliance

Control Protocol	LAN (TCP/IP), RS-232 (bi-directional), RS-485 (bi-directional)
------------------	--

Communications & Control

Control Ports	LAN, RS-232, RS-485
Control Connector Type	RJ45, Mini phoenix (3.81mm)

Mechanical Features

Touch Panel Size	10 in
Touch Panel Resolution	1280x800
Touch Type	Capacitive Touch Screen
Network Port	LAN (RJ45)
RS-232/485 Port	1 x 3-pin - 3.81mm phoenix connector

Power

Power Input	PoE (IEEE 802.3af), DC 24V/1A via 2-pin phoenix
Power Consumption	6W (max)

Enclosure

Mounting Option	Table
Product Dimensions (W × D × H)	9.66 in × 6.46 in × 1.06 in (245.36mm × 164.08mm × 26.92mm)
Weight	1.96 lbs (889g)

Warranty

Parts	5 year
Labor	5 year

ICON-E1

Standards & Compliance

Control Protocol	LAN (TCP/IP), RS-232 (bi-directional), IR, I/O
------------------	--

Communications & Control

Control Ports	LAN, RS-232, IR, I/O, RS-485
Control Connector Type	RJ45, Mini phoenix (3.81mm)

Power

Power Input	PoE (IEEE 802.3af), 12-24V DC / 1A via 2-pin phoenix
Power Consumption	6W (max)

Enclosure

Product Dimensions (W x D x H)	3.69 in x 2.63 in x 0.38 in (93.7mm x 66.8mm x 9.7mm)
Weight	0.65 lbs (295g)

Warranty

Parts	5 year
Labor	5 year

PS-610

Standards & Compliance

Signal Standards	HDMI 2.0, USB 3.0, DP-Alt Mode, HDBaseT 3.0
HDCP	HDCP 2.2

Connector Types

HDMI Inputs	3 x HDMI IN (Type A, 19-pin female)
HDMI Outputs	1 x HDMI OUT (Type A, 19-pin female)
HDBaseT Out	1 x HDBaseT (RJ45)
USB Input	2 x USB IN (USB-C)
USB Output	1 x USB OUT (USB-B)
Control	LAN (RJ45), RS-232 3-pin - 3.81mm phoenix connector (bi-directional)
Audio Inputs	Analog (stereo balanced)
Audio Outputs	Analog (stereo balanced)
Dante	Yes

Performance

Max Video Resolution	4K60 (4:4:4)
Video Bandwidth	12 Gbps
PIP	Split-screen, Windowed
HDMI Audio Format	LPCM

Communications & Control

Control Ports	LAN, RS-232, IR
IR Remote	Yes
Control Connector Type	RJ45, Mini phoenix (3.81mm), 3.5mm TRS

Power

Power Input	DC 24V/8A (US/EU standard, CE/FCC/UL certified)
Power Supply	AC 100 - 240V 50/60Hz
Power Consumption	150W (max)

Enclosure

Product Dimensions (W × D × H)	TX: 8.66 in × 5.91 in × 1.73 in (219.96mm × 150.11mm × 43.94mm) RX: 5.51 in × 4.13 in × 0.85 in (140.01mm × 104.90mm × 21.59mm)
Weight	TX: 2.67 lbs (1211g) RX: 0.93 lbs (422g)

Warranty

Parts	5 year
Labor	5 year

TL-SG108PE 8 port switch**Connector Types & Features**

Ports	4 x PoE+ ports, 8 x Gigabit RJ45 ports
Switching Capacity	16 Gbps
Packet Forwarding Rate	11.9 Mpps
Packet Buffer Memory	1.5 Mb
Jumbo Frame	15 KB

Power

Power Consumption	74.27W (max)
-------------------	--------------

Enclosure

Product Dimensions (W × D × H)	6.2 in × 4.0 in × 1.0 in (158mm × 101mm × 25mm)
--------------------------------	---

Warranty

Parts	3 year
Labor	3 year