



[View product details](#)

PureLink's PushGo Stowe defines the high end of intelligent, plug-and-play performance for executive boardrooms and large collaboration spaces. Ready for same-day setup, it delivers the clarity, control, and refinement expected in a premium professional environment. At its core is a professional 4K PTZ camera with 20x optical zoom, capturing every participant in sharp, true-to-life detail. Audio performance is powered by Dante-enabled architecture, a 150W amplifier, and integrated DSP that fills the room with clean, natural sound. The 10" touchscreen offers complete precision control — from switching inputs and adjusting camera settings to managing displays, sound, and lighting. Users can easily create and recall camera presets directly from the touchscreen for quick, consistent framing in any meeting. A secondary wall-mounted touchscreen scheduling panel syncs with your calendar to display real-time room availability and enable quick, seamless reservations. PushGo Stowe is a complete, luxury-grade system engineered to deliver flawless meetings with effortless control and striking visual clarity.

Customization Available: Enjoy complimentary logo placement on your touchscreen. After your order, we'll contact you to finalize details. Additional interface or hardware customizations are available for an added cost.

Key Features

- Fully pre-programmed and ready to use
- Plug-and-play for same-day setup
- Premium 10" touchscreen control
- Professional 4K PTZ camera with 20x optical and 8x digital zoom
- Integrated Dante audio with 150W amplifier and DSP
- Supports up to six HDMI or USB-C devices
- Room scheduling touchscreen with calendar integration
- Don't Blink™ Switching for seamless, instant source transitions
- Works with Zoom, Microsoft Teams, Webex, Google Meet, and more
- Includes all essential hardware and cables
- Complimentary logo branding on touchscreen
- Perfect for executive offices, boardrooms, training spaces, and more

Specifications

ICON-T10

Standards & Compliance

Control Protocol	LAN (TCP/IP), RS-232 (bi-directional), RS-485 (bi-directional)
------------------	--

Communications & Control

Control Ports	LAN, RS-232, RS-485
Control Connector Type	RJ45, Mini phoenix (3.81mm)

Mechanical Features

Touch Panel Size	10 in
Touch Panel Resolution	1280x800
Touch Type	Capacitive Touch Screen
Network Port	LAN (RJ45)
RS-232/485 Port	1 x 3-pin - 3.81mm phoenix connector

Power

Power Input	PoE (IEEE 802.3af), DC 24V/1A via 2-pin phoenix
Power Consumption	6W (max)

Enclosure

Mounting Option	Table
Product Dimensions (W × D × H)	9.66 in × 6.46 in × 1.06 in (245.36mm × 164.08mm × 26.92mm)
Weight	1.96 lbs (889g)

Warranty

Parts	5 year
Labor	5 year

ICON-E1

Standards & Compliance

Control Protocol	LAN (TCP/IP), RS-232 (bi-directional), IR, I/O
------------------	--

Communications & Control

Control Ports	LAN, RS-232, IR, I/O, RS-485
Control Connector Type	RJ45, Mini phoenix (3.81mm)

Power

Power Input	PoE (IEEE 802.3af), 12-24V DC / 1A via 2-pin phoenix
Power Consumption	6W (max)

Enclosure

Product Dimensions (W × D × H)	3.69 in × 2.63 in × 0.38 in (93.7mm × 66.8mm × 9.7mm)
Weight	0.65 lbs (295g)

Warranty

Parts	5 year
Labor	5 year

PS-610

Standards & Compliance

Signal Standards	HDMI 2.0, USB 3.0, DP-Alt Mode, HDBaseT 3.0
HDCP	HDCP 2.2

Connector Types

HDMI Inputs	3 x HDMI IN (Type A, 19-pin female)
HDMI Outputs	1 x HDMI OUT (Type A, 19-pin female)
HDBaseT Out	1 x HDBaseT (RJ45)
USB Input	2 x USB IN (USB-C)
USB Output	1 x USB OUT (USB-B)
Control	LAN (RJ45), RS-232 3-pin - 3.81mm phoenix connector (bi-directional)
Audio Inputs	Analog (stereo balanced)
Audio Outputs	Analog (stereo balanced)
Dante	Yes

Performance

Max Video Resolution	4K60 (4:4:4)
Video Bandwidth	12 Gbps
PIP	Split-screen, Windowed
HDMI Audio Format	LPCM

Communications & Control

Control Ports	LAN, RS-232, IR
IR Remote	Yes
Control Connector Type	RJ45, Mini phoenix (3.81mm), 3.5mm TRS

Power

Power Input	DC 24V/8A (US/EU standard, CE/FCC/UL certified)
Power Supply	AC 100 - 240V 50/60Hz
Power Consumption	150W (max)

Enclosure

Product Dimensions (W x D x H)	TX: 8.66 in x 5.91 in x 1.73 in (219.96mm x 150.11mm x 43.94mm) RX: 5.51 in x 4.13 in x 0.85 in (140.01mm x 104.90mm x 21.59mm)
Weight	TX: 2.67 lbs (1211g) RX: 0.93 lbs (422g)

Warranty

Parts	5 year
Labor	5 year

NICGIGA 16 port PoE Switch

Standards & Compliance

Standard	IEEE 802.3af/at compliant
----------	---------------------------

Connector Types & Features

Switch Type	Unmanaged, plug-and-play
Ports	16 x PoE+ ports, 2 x Gigabit uplink ports, 1 x SFP port
Switching Capacity	12 Gbps

Power

Power Consumption	250W (max)
-------------------	------------

Warranty

Parts	3 year
Labor	3 year

VIP-CAM-30-20X

Standards & Compliance

Signal Standards	HDMI 1.3
HDCP	HDCP 1.4

Connector Types

HDMI Outputs	1 x HDMI OUT (Type A, 19-pin female)
USB Output	USB-B

Performance

PTZ	Yes
Focal Length	f = 4.7 mm – 94.0 mm
Protocols	RTSP, RTMP, ONVIF
Field of View	2.9° to 59.5°
Iris	F1.6 – F3.5
Minimum Illumination	0.5 Lux (Color), 0.1 Lux (B/W)
Lens Zoom	20× Optical, 8× Digital
PoE Support	IEEE 802.3af / IEEE 802.3at (PoE / PoE+)

Communications & Control

Control Ports	LAN, RS-232, IR
Control Connector Type	RJ45, 8-pin mini-DIN connector

Enclosure

Rack Mounting Option	Wall, Ceiling
Product Dimensions (W × D × H)	8.9 in × 6.2 in × 8.1 in (226mm × 157mm × 206mm)
Weight	3.75 lbs (1701g)

Warranty

Parts	5 year
Labor	5 year

DIO-AMP150

Standards & Compliance

Signal Standards	Dante, AES67
Amplifier Type	Class D

Connector Types

Line In	1 x Line In 5-pin 3.81mm phoenix connector
Line Out	1 x Line Out 5-pin 3.81 phoenix connector 1 x 4/8Ω AMP OUT MSTB 2,5/4-GF-5.08 1 x 70V/100V AMP OUT MSTB 2,5/4-GF-5.08

Performance

Amplifier Output (W)	150W single-channel, 75W two-channel
Dante Port	Single
DSP	Yes

Communications & Control

Control Ports	LAN, RS-232
Network	Dante® AES67
Control Connector Type	RJ45, Mini phoenix (3.81mm)

Power

Power Consumption	150W (max)
-------------------	------------

Enclosure

Rack Mounting Option	Yes
----------------------	-----

Warranty

Parts	5 year
Labor	5 year

RoomView-110W

Mechanical Features

Touch Panel Size	10 in
Touch Panel Resolution	1280x800
RS-232/485 Port	1 x 3-pin - 3.81mm phoenix connector
Control	LAN (RJ45), RS-232 3-pin - 3.81mm phoenix connector (bi-directional)

Power

Power Input	POE, 24V DC/1A 1 x 2 phoenix connector
Power Consumption	6W (max)

Enclosure

Rack Mounting Option	Wall
----------------------	------

Warranty

Parts	5 year
Labor	5 year