

[View product details](#)



iCON™ **USB-C** **HDMI®** **4K**

PureLink’s PushGo Taos is built for dynamic collaboration — transforming shared workspaces, classrooms, and creative studios into flexible, multi-user environments. Pre-programmed and ready out of the box, Taos makes real-time collaboration effortless. Its advanced multi-viewer supports up to eight simultaneous connections via HDMI, USB-C, VGA, or wireless input. Wireless connectivity includes direct casting from iPhone and Android devices, as well as dongle-based connections for Windows and Mac computers. Multiple users can share their screens at once — displayed side by side or spotlighted individually — making it ideal for brainstorming sessions, project reviews, or hybrid learning spaces. The 10” touchscreen controller provides fluid, one-touch management of layouts, sources, and display modes. With vivid video output and precise, balanced sound, PushGo Taos turns any workspace into a hub for intelligent, connected collaboration.

Customization Available: Enjoy complimentary logo placement on your touchscreen. After your order, we’ll contact you to finalize details. Additional interface or hardware customizations are available for an added cost.

Key Features

- Fully pre-programmed and ready to use
- Plug-and-play for same-day setup
- Premium 10” touchscreen control
- Stunning 4K video and high-quality audio output
- Supports up to eight HDMI, USB-C, or VGA devices
- Multi-view layouts for sharing multiple screens at once
- Wireless and wired connectivity options
- Works with Zoom, Microsoft Teams, Google Meet, GoToMeeting, and more
- Includes all essential hardware and cables
- Complimentary logo branding on touchscreen
- Perfect for huddle rooms, classrooms, collaborative workspaces, and more

Specifications

ICON-T10

Standards & Compliance

Control Protocol	LAN (TCP/IP), RS-232 (bi-directional), RS-485 (bi-directional)
------------------	--

Communications & Control

Control Ports	LAN, RS-232, RS-485
Control Connector Type	RJ45, Mini phoenix (3.81mm)

Mechanical Features

Touch Panel Size	10 in
Touch Panel Resolution	1280x800
Touch Type	Capacitive Touch Screen
Network Port	LAN (RJ45)
RS-232/485 Port	1 x 3-pin - 3.81mm phoenix connector

Power

Power Input	PoE (IEEE 802.3af), DC 24V/1A via 2-pin phoenix
Power Consumption	6W (max)

Enclosure

Mounting Option	Table
Product Dimensions (W × D × H)	9.66 in × 6.46 in × 1.06 in (245.36mm × 164.08mm × 26.92mm)
Weight	1.96 lbs (889g)

Warranty

Parts	5 year
Labor	5 year

ICON-E1**Standards & Compliance**

Control Protocol	LAN (TCP/IP), RS-232 (bi-directional), IR, I/O
------------------	--

Communications & Control

Control Ports	LAN, RS-232, IR, I/O, RS-485
Control Connector Type	RJ45, Mini phoenix (3.81mm)

Power

Power Input	PoE (IEEE 802.3af), 12-24V DC / 1A via 2-pin phoenix
Power Consumption	6W (max)

Enclosure

Product Dimensions (W × D × H)	3.69 in × 2.63 in × 0.38 in (93.7mm × 66.8mm × 9.7mm)
Weight	0.65 lbs (295g)

Warranty

Parts	5 year
Labor	5 year

TL-SG108PE 8 port switch**Connector Types & Features**

Ports	4 x PoE+ ports, 8 x Gigabit RJ45 ports
Switching Capacity	16 Gbps
Packet Forwarding Rate	11.9 Mpps
Packet Buffer Memory	1.5 Mb
Jumbo Frame	15 KB

Power

Power Consumption	74.27W (max)
-------------------	--------------

Enclosure

Product Dimensions (W × D × H)	6.2 in × 4.0 in × 1.0 in (158mm × 101mm × 25mm)
--------------------------------	---

Warranty

Parts	3 year
Labor	3 year

Collabora-8-4K

Standards & Compliance

Signal Standards	HDMI 2.0b, VGA
HDCP	HDCP 2.2

Connector Types

HDMI Inputs	2 x HDMI IN (Type A, 19-pin female)
HDMI Outputs	2 x HDMI OUT (Type A, 19-pin female)
VGA Input	1 x VGA IN (DB15)
HDBaseT Out	1 x HDBaseT (RJ45)
USB Input	1 x USB IN (USB-C), 3 x USB-A, 2 x USB-B
Control	LAN (RJ45), RS-232 3-pin - 3.81mm phoenix connector (bi-directional)
Audio Inputs	Analog (stereo balanced)
Audio Outputs	Analog (stereo balanced)

Performance

Max Video Resolution	3840x2160p60
Video Bandwidth	12 Gbps
HDMI Audio Format	PCM 2.0

Communications & Control

Control Ports	IR, RS-232 (bi-directional), LAN (TCP/IP)
IR Remote	Yes
Control Connector Type	RJ45, Mini phoenix (3.81mm), 3.5mm TRS

Power

Power Supply	DC 12V/1.0A
Power Consumption	20W (max)

Enclosure

Rack Mounting Option	No
Product Dimensions (W x D x H)	8.46 in x 1.65 in x 5.52 in (214.88mm x 41.91mm x 140.21mm)
Weight	2.2 lbs (998g)

Warranty

Parts	5 year
Labor	5 year

Collabora-8-4K-Dongle-2

Standards & Compliance

Signal Standards	HDMI 2.0b
------------------	-----------

Connector Types

HDMI Inputs	1 x HDMI IN (Type A, 19-pin female)
USB Input	1 x USB IN (USB-C), 1 x USB IN (USB-A)

Warranty

Parts	5 year
Labor	5 year