

[View product details](#)



iCON™ **USB-C** **HDMI** **4K** **Dante®**

PureLink's PushGo Vail is a complete meeting system crafted for premium remote collaboration. Arriving fully pre-configured, it is ready to use the same day – simply plug in your devices and power on to get started. PushGo Vail combines a 4K PTZ camera, beamforming microphone array, and integrated soundbar in a single, elegant unit that automatically tracks the active speaker and keeps every participant perfectly framed. Its Smart Gallery mode creates individual video tiles for each attendee, bringing greater clarity and presence to virtual meetings. Controlled from the 10" touchscreen, users can easily adjust volume, fine-tune camera angles, and manage lighting – all from one intuitive interface. Compatible with Zoom, Microsoft Teams, and Google Meet, PushGo Vail delivers professional-grade video meetings that feel natural, lifelike, and beautifully unified.

Customization Available: Enjoy complimentary logo placement on your touchscreen. After your order, we'll contact you to finalize details. Additional interface or hardware customizations are available for an added cost.

Key Features

- Fully pre-programmed and ready to use
- Plug-and-play for same-day setup
- Premium 10" touchscreen control
- All-in-one 4K PTZ camera, microphone, and soundbar
- AI auto-tracking and Smart Gallery view
- Supports up to six HDMI or USB-C devices
- Don't Blink™ Switching for seamless, instant source transitions
- Works with Zoom, Microsoft Teams, Google Meet, GoToMeeting, and more
- Includes all essential hardware and cables
- Complimentary logo branding on touchscreen
- Perfect for hybrid meeting rooms, executive offices, small conference spaces, and more

Specifications

ICON-T10

Standards & Compliance

Control Protocol	LAN (TCP/IP), RS-232 (bi-directional), RS-485 (bi-directional)
------------------	--

Communications & Control

Control Ports	LAN, RS-232, RS-485
Control Connector Type	RJ45, Mini phoenix (3.81mm)

Mechanical Features

Touch Panel Size	10 in
Touch Panel Resolution	1280x800
Touch Type	Capacitive Touch Screen
Network Port	LAN (RJ45)
RS-232/485 Port	1 x 3-pin - 3.81mm phoenix connector

Power

Power Input	PoE (IEEE 802.3af), DC 24V/1A via 2-pin phoenix
Power Consumption	6W (max)

Enclosure

Mounting Option	Table
Product Dimensions (W × D × H)	9.66 in × 6.46 in × 1.06 in (245.36mm × 164.08mm × 26.92mm)
Weight	1.96 lbs (889g)

Warranty

Parts	5 year
Labor	5 year

ICON-E1

Standards & Compliance

Control Protocol	LAN (TCP/IP), RS-232 (bi-directional), IR, I/O
------------------	--

Communications & Control

Control Ports	LAN, RS-232, IR, I/O, RS-485
Control Connector Type	RJ45, Mini phoenix (3.81mm)

Power

Power Input	PoE (IEEE 802.3af), 12-24V DC / 1A via 2-pin phoenix
Power Consumption	6W (max)

Enclosure

Product Dimensions (W × D × H)	3.69 in × 2.63 in × 0.38 in (93.7mm × 66.8mm × 9.7mm)
Weight	0.65 lbs (295g)

Warranty

Parts	5 year
Labor	5 year

PS-610

Standards & Compliance

Signal Standards	HDMI 2.0, USB 3.0, DP-Alt Mode, HDBaseT 3.0
HDCP	HDCP 2.2

Connector Types

HDMI Inputs	3 x HDMI IN (Type A, 19-pin female)
HDMI Outputs	1 x HDMI OUT (Type A, 19-pin female)
HDBaseT Out	1 x HDBaseT (RJ45)
USB Input	2 x USB IN (USB-C)
USB Output	1 x USB OUT (USB-B)
Control	LAN (RJ45), RS-232 3-pin - 3.81mm phoenix connector (bi-directional)
Audio Inputs	Analog (stereo balanced)
Audio Outputs	Analog (stereo balanced)
Dante	Yes

Performance

Max Video Resolution	4K60 (4:4:4)
Video Bandwidth	12 Gbps
PIP	Split-screen, Windowed
HDMI Audio Format	LPCM

Communications & Control

Control Ports	LAN, RS-232, IR
IR Remote	Yes
Control Connector Type	RJ45, Mini phoenix (3.81mm), 3.5mm TRS

Power

Power Input	DC 24V/8A (US/EU standard, CE/FCC/UL certified)
Power Supply	AC 100 - 240V 50/60Hz
Power Consumption	150W (max)

Enclosure

Product Dimensions (W × D × H)	TX: 8.66 in × 5.91 in × 1.73 in (219.96mm × 150.11mm × 43.94mm) RX: 5.51 in × 4.13 in × 0.85 in (140.01mm × 104.90mm × 21.59mm)
Weight	TX: 2.67 lbs (1211g) RX: 0.93 lbs (422g)

Warranty

Parts	5 year
Labor	5 year

TL-SG108PE 8 port switch

Connector Types & Features

Ports	4 x PoE+ ports, 8 x Gigabit RJ45 ports
Switching Capacity	16 Gbps
Packet Forwarding Rate	11.9 Mpps
Packet Buffer Memory	1.5 Mb
Jumbo Frame	15 KB

Power

Power Consumption	74.27W (max)
-------------------	--------------

Enclosure

Product Dimensions (W × D × H)	6.2 in × 4.0 in × 1.0 in (158mm × 101mm × 25mm)
--------------------------------	---

Warranty

Parts	3 year
Labor	3 year

HUDDLE-CAM-500

Standards & Compliance

Signal Standards	HDMI 2.0, USB-A, USB-C (DP-Alt Mode)
HDCP	HDCP 1.4, HDCP 2.2
Regulatory Certifications	CE, FCC, RoHS

Connector Types

HDMI Outputs	1 x HDMI OUT (Type A, 19-pin female)
USB Output	USB-C (DP-Alt Mode), USB-A

Communications & Control

Control Ports	LAN, RS-232
Control Connector Type	RJ45, 8-pin mini-DIN connector

Enclosure

Rack Mounting Option	Wall, Ceiling
Product Dimensions (W x D x H)	8.9 in x 6.2 in x 8.1 in (226.06mm x 157.48mm x 205.74mm)
Weight	3.75 lbs (1701g)

Warranty

Parts	5 year
Labor	5 year