

# UX-4400 4x4 4K HDMI Matrix Switcher with HDCP 2.2



The **UX-4400** provides switching of up to four HDMI 2.0 inputs and outputs with advanced EDID management and HDCP 2.2 compliance. The UX-4400 offers full Ultra HD/4K support and multiple control options including RS-232C and LAN ports. PureLink's legendary EDID management system ensures compatibility across multiple display types and delivers consistent connectivity with quick, clean switching from source to display for a seamless presentation experience.

## Key Features

- 4x4 HDMI 2.0 matrix switching
- Resolutions up to 4K@50/60 Hz (4:4:4 pixel format)
- HDMI 2.0, HDCP 2.2 support
- Advanced EDID Management
- Bi-directional RS232/LAN control
- Locking HDMI ports

## Technical Specifications

### CONNECTOR TYPES

(4) HDMI Input  
(4) HDMI Output  
(1) RS-232C Serial  
(1) LAN (TCP/IP)

### SUPPORTED RESOLUTIONS

Up to Ultra HD/4K  
4096 x 2160 @50/60Hz (RGB 4:4:4  
YCbCr 4:4:4, 4:2:2, 4:2:0)

### DATA RATE

18 Gbps

### SUPPORTED FORMATS

HDMI 2.0, HDCP 2.2

### OPERATING TEMPERATURE

32° F to 104° F (0° to 47° C)

### STORAGE TEMPERATURE

-40° F to 158° F (-40° to 70° C)

### HUMIDITY

0 ~ 90% non-condensing

### MTBF

95,000 hours

### POWER CONSUMPTION

60W (DC + 12V 5.0A power supply)

### DIMENSIONS

19" x 8.0" x 1.75" in.  
(482.6 x 203.2 x 44.45 mm)

### WEIGHT

6.7 lbs (3.04 kg)

