



[View product details](#)

EZControl™



iCON-10W provides a compact, powerful 10-button control solution for LAN and RS-232-enabled devices. With a built-in web UI programming interface, it allows integrators to configure macros of up to six commands per button, enabling precise, efficient control in any environment.

The iCON-10W also offers optional pre-programming for PureLink products, delivering a plug-and-play experience right out of the box. Multiple units can be combined for larger control panels, while preconfigured or custom button labels streamline installation, making iCON-10W ideal for conference rooms, classrooms, or any AV system requiring reliable tactile control.

## Key Features

- 10-button control panel with integrated LAN and RS-232 control
- Built-in web UI programming interface for fast configuration
- Macros allow up to 6 commands per button
- PoE (IEEE 802.3af) for simplified installation
- Optional pre-programming services for plug-and-play setup
- Multiple units can be combined for larger panels
- Optional preconfigured or custom button labels

## Specifications

---

### Standards & Compliance

Control Protocol	RS-232 (bi-directional), Telnet, LAN (TCP/IP)
------------------	---

---

### Communications & Control

Control Ports	LAN, RS-232
Control Connector Type	RJ45, Mini Phoenix (3.81mm)

---

### Power

Network Port	LAN (RJ45)
RS-232/485 Port	1 × 3.81mm Phoenix Connector (3-pin)
ESD Protection	Human Body Model (±8 kV)
Power Input	PoE (IEEE 802.3af), DC 12-24V/1A via 2-pin Phoenix
Power Supply	DC 12V/0.5A
Power Consumption	1.3W (max)

---

### Environment

Operating Temperature	32 to 113°F / 0 to 45°C
Storage Temperature	-4 to 158°F / -20 to 70°C
Relative Humidity	10 to 90% RH (no condensation)

---

### Enclosure

Mounting Option	Wall
Product Dimensions (W × D × H)	1.77 in × 1.42 in × 4.16 in (45mm × 36mm × 105.6mm)
Weight	0.40 lbs (181.44g)

---

### Warranty

Parts	5 year
Labor	5 year

---